



DESCRIPTION

- **MS Acryl** is a universally applicable plastic latex for the improvement of mortars and sealing slurries.

ADVANTAGES

- Increases flexibility.
- Improves adhesion.
- Reduces the risk of cracking

APPLICATION AREA

MS Acryl enhances mortars to increase flexibility and adhesion on problem substrates.

PRODUCT INFORMATION

Packaging

Can of 10 kg; 60 x 10 kg pallet

Storage and shelf life

Store frost-free and cool.
If stored in closed packaging and in a dry place, the product has a shelf life of approx. 12 months.

Consumption

Add 10-20% to the mixing water. As adhesive primer: dilute 1:2 with water.

MS Acryl

TECHNICAL DATA	
Density	approx. 1.0 kg/L
Solid content	approx. 45%

APPLICATION
<u>SURFACE PREPARATION</u> All mineral substrates except gypsum. The substrates may be dry or moist
<u>PROCESSING OF MS Acryl</u> MS Acryl : add 10-20% to the mixing water. As adhesive primer: dilute in a ratio of 1:2 with water. Clean tools with water. Temperature conditions: Between +5°C to max 30°C

TRANSPORT
Non-hazardous material

TOOLS
Brush, roller or spray equipment

SAFETY
Wear suitable gloves and safety glasses. For more information on safety considerations related to handling, transporting, storing and disposing of the materials, we recommend consulting our safety data sheet.

MS Acryl

Legal notice:

Please note that the information and data provided are given in good faith based on our current knowledge, laboratory calculations and practical experience, and serve as general guidelines. They do not constitute binding principles and may not cover every individual case due to varying working conditions, materials and construction sites. Therefore, anyone intending to use the product should check in advance that it is suitable for the intended application. Our products and their use are described in a general context, and it is recommended to carry out tests or contact us if in doubt. Unless we explicitly give written guarantees regarding the suitability of the product for a contracted use, technical advice or instructions are not binding. All orders are accepted subject to our current terms and conditions of sale and delivery.

