



DESCRIPTION

- **MS Floor primer** is an aqueous, solvent-free, one-component synthetic resin dispersion

ADVANTAGES

- Alkali-resistant
- Very good adhesion
- Quickly reworkable
- Pore-sealing

FIELD OF USE

MS Floor primer is a fast-drying, one-component bonding agent based on an aqueous synthetic resin dispersion, produced without the use of solvents. **MS Floor primer** can be used both as a bonding agent on pre-treated metal surfaces and, when diluted with water, as a bonding primer on cementitious substrates. The product is characterized by its particularly good adhesion and quick drying time.

PRODUCT INFORMATION

Packaging

10 kg can; 30 X 10 kg cans / pallet

Water dilutable

Maximum 1: 2 dilutable with water

Storage and shelf life

Store in frost free and dry conditions. Protect from rain, condensation and high humidity. If stored in an unopened bag and in a dry place, the product will keep for approx. 12 months.

Consumption

50 - 120 gr/m²

MS Floor primer

TECHNICAL DATA	
VOC content	0,00 g/L
Density	1,01 g/cm ³ (DIN EN ISO 1183-1)
Solid content	45%
pH value	8 - 9
Walkable (at 20°C and 80% RH)	After approx. 2 hours
Dry film thickness	25 - 60 µm

APPLICATION
<u>PREPARATION OF SURFACE</u> The surface must be dry, clean and free from oils and fats. The surface temperature must be > 5°C. The suitability and condition of the surface must always be checked before applying MS Floor primer.
<u>MIX AND APPLY MS Floor primer</u> MS Floor primer can be diluted max. 1:2 with water. Mix MS Floor primer carefully before applying with a roller or a brush. The color will change from milky-blue to transparent-blue. Apply subsequent coatings immediately when the MS Floor primer is dry. Temperature conditions: Between +5°C to max 30°C The cleaning of the tools can be done immediately with water.

MS Floor primer

TRANSPORT

Non-hazardous material

TOOLS

Mixer, paint roller, paint brush

SAFETY

Wear protective goggles and appropriate gloves. For additional information regarding the safety considerations associated with handling, transporting, storing, and disposing of the materials, we recommend consulting our Safety Data Sheet.

Legal notice :

Please be advised that the information and data provided are given in good faith based on our current knowledge, laboratory calculations and real-life experiences, serving as general guidelines. They are not binding principles and may not cover every individual case due to diverse working conditions, materials, and construction sites. For this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. Our products and their usage are described in a general context, and it is recommended to conduct tests or consult with us if there are any doubts. Unless we explicitly provide written assurance regarding the product's suitability for a contractually stipulated intended use, any technical advice or instruction is non-binding. All orders are accepted subject to our current terms of sale and delivery.

